

LED napájecí zdroje

STR. 1/2

LED I-Panel napájení

40000522

EAN: 8720604740219

ALTERNATIVA K PŮVODNÍM ZAPUŠTĚNÝM FLUORESCENČNÍM SVÍTIDLŮM

LED napájecí zdroje Prolumia jsou k dispozici pro vnitřní i venkovní použití (voděodolné). Díky tenkému provedení mohou být zdroje Prolumia snadno uloženy například pod police, do skříně nebo za stěnou.



VLASTNOSTI PRODUKTU

Model	Dynamic	Output voltage	2 44 Volt
Suitable for outdoor use	✗	Output current	1250 1250 Milliampere
Dimming 0-10 V	✗	Output power	55 55 Watt
Dimming 1-10 V	✓	Length	127 Millimetre
Dimming DALI	✓	Width	75 Millimetre
Dimming DMX	✗	Height	30 Millimetre
Dimming GPRS	✗		
Dimming DSI	✗		
Dimming LineSwitch	✗		
Dimming mains voltage modulation	✗		
Dimming manufacturer's proprietary system	✗		
Dimming phase cut-off (trailing edge)	✗		
Dimming phase cut-on (leading edge)	✗		
Dimming potentiometer (integrated)	✗		
Dimming programmable	✗		
Dimming RF	✗		
Dimming Sine Wave Reduction	✗		
Dimming Touch and Dim	✗		
Dimming with push-button	✓		
No dim function	✗		
Dimming Zigbee	✗		
Constant light output (CLO)	✗		
Housing	Plastic housing		
Suitable for constant current	✓		
Suitable for constant voltage	✗		
Suitable for DC-voltage (primary side)	✗		
Degree of protection (IP)	IP20		
Protection class according to IEC 61140	II		
Operation by Bluetooth	✗		
Compatible with Apple HomeKit	✗		

LED napájecí zdroje

PAGINA 2/2

LED I-Panel napájení

40000522

EAN: 8720604740219

VLASTNOSTI PRODUKTU

(Pokračování)

Compatible with Google Assistant	✕
Compatible with Amazon Alexa	✕
Compatible with Casambi	✕
IFTTT support available	✕