PROLUMIA®

LED I-Panel

LED I-Panel napájení

40000523
EAN: 8720604740226

ALTERNATIVA K PŮVODNÍM ZAPUŠTĚNÝM FLUORESCENČNÍM SVÍTIDLŮM

Řada svítidel LED I-Panel je výbornou LED alternativou k tradičním vestavným fluorescenčním svítidlům. Úzké linie a nízká montážní výška dávají této řadě moderní a nadčasový charakter. Díky různým možnostem instalace: zapuštění, instalace na povrch nebo zavěšení, jsou vhodná pro širokou škálu aplikací.

VLASTNOSTI PRODUKTU

Model	Dynamic
Suitable for outdoor use	✖
Dimming 0-10 V	✖
Dimming 1-10 V	✔
Dimming DALI	✖
Dimming DMX	✖
Dimming GPRS	✖
Dimming DSI	✖
Dimming LineSwitch	✖
Dimming mains voltage modulation	✖
Dimming manufacturer's proprietary system	✖
Dimming phase cut-off (trailing edge)	✖
Dimming phase cut-on (leading edge)	✖
Dimming potentiometer (integrated)	✖
Dimming programmable	✖
Dimming RF	✖
Dimming Sine Wave Reduction	✖
Dimming Touch and Dim	✖
Dimming with push-button	✔
No dim function	✖
Dimming Zigbee	✖
Constant light output (CLO)	✖
Housing	Plastic housing
Suitable for constant current	✔
Suitable for constant voltage	✖
Suitable for DC-voltage (primary side)	✖
Degree of protection (IP)	IP20
Protection class according to IEC 61140	II
Operation by Bluetooth	✖
Compatible with Apple HomeKit	✖

Output voltage	2|53	Volt
Output current	250|900	Milliampere
Output power	13|32	Watt
Length	105	Millimetre
Width	66	Millimetre
Height	22	Millimetre

PROLUMIA®

LED I-Panel

LED I-Panel napájení

40000523
EAN: 8720604740226

VLASTNOSTI PRODUKTU
(Pokračování)

Compatible with Google Assistant	✖
Compatible with Amazon Alexa	✖
Compatible with Casambi	✖
IFTTT support available	✖