


LED Pro-Ceiling ø 240 mm (přisazené)

40001725

EAN: 8721063000081

VYCHUTNEJTE SI TEPLU DEKORATIVNÍHO SVĚTLA V KOMBINACI S RAFINOVANOSTÍ MODERNÍHO DESIGNU

Řada Prolumia Pro-Ceiling je jedinečná svým designem. Spojuje v sobě teplo dekorativního světla s rafinovaností moderního designu. K dispozici je kulatý, čtvercový nebo obdélníkový tvar a různé velikosti pro zapuštěnou instalaci nebo povrchovou montáž na strop nebo stěnu. Řada Pro-Ceiling má životnost více než 50 000 hodin, dodává se s integrovaným napájecím zdrojem a její instalace je rychlá a snadná!



VLASTNOSTI PRODUKTU

Suitable for wall mounting	✓	Suitable for number of light sources	1
Suitable for wall mounting	✓	LED nominal current at constant current	200 350 Milliampere
Suitable for suspended mounting	✗	Nominal voltage	220 240 Volt
Suitable for ceiling mounting	✓	Nominal current	200 350 Milliampere
Suitable for built-in mounting	✗	Rated lifetime L80/B50 at 25 °C	111000 Hour
Suitable for surface mounting	✓	Rated lifetime L70/B50 at 25 °C	177000 Hour
Suitable for light line configuration	✗	Rated life time L70/B10 at 25 °C	142000 Hour
Suitable for workplace according to EN 12464-1	✗	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq)	93 Percentage
Lamp type	LED not exchangeable	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	91 Percentage
With light source	✓	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq)	85 Percentage
Lamp holder	Other	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq)	0 Percentage
Housing material	Aluminium	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	0 Percentage
Surface protection housing	Powder coating	Rated life time L80/B10 at 25 °C	89000 Hour
Housing colour	Black	Rated life time L90/B10 at 25 °C	43000 Hour
Material cover	Plastic, opal	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq)	0 Percentage
Type of grid	None	Rated life time L90/B50 at 25 °C	53000 Hour
Voltage type	AC	Max. number of luminaires per miniature circuit breaker B16 (MCB)	60
Type of control gear	LED operating device current-controlled	Max. number of luminaires per miniature circuit breaker C16 (MCB)	102
With control gear	✓	Rated ambient temperature according to IEC 62722-2-1	-10 40 Degrees celsius
Exchangeable control gear	✓	Luminaire efficacy	84 Lumen/Watt
Dimmable	✓	Rated luminous flux according to IEC 62722-2-1	1300 Lumen
Dimming 0-10 V	✗	Suitable for lamp power	7,8 13,63 Watt
Dimming 1-10 V	✗	Luminaire efficacy	83 84 Lumen/Watt
Dimming DALI	✗	Max. system power	15 Watt

LED Pro-Ceiling

PAGINA 2/3

LED Pro-Ceiling ø 240 mm (přisazené)

40001725

EAN: 8721063000081

VLASTNOSTI PRODUKTU

(Pokračování)

Dimming DALI-2	✗	Rated luminous flux according to IEC 62722-2- 1	650 1150 Lumen
Dimming DMX	✗	Colour temperature	2700 4000 Kelvin
Dimming GPRS	✗	Flickering value Pst LM	0,01
Dimming LineSwitch	✗	Power factor	0,92
Dimming DSI	✗	Stroboscope effect value SVM	0,4
Dimming manufacturer's proprietary system	✗	Height/depth	39 Millimetre
Dimming mains voltage modulation	✗	Outer diameter	240 Millimetre
Dimming phase cut-off (trailing edge)	✓	Total harmonic distortion	20
Dimming phase cut-on (leading edge)	✓	Number of poles	2
Dimming programmable	✗	Conductor cross section	2,5 Square millimetre
Dimming potentiometer (integrated)	✗	Unified Glare Ratio (UGR)	22
Dimming RF	✗		
Dimming Sine Wave Reduction	✗		
Dimming Touch and Dim	✗		
Dimming Zigbee	✗		
Dimming with push-button	✗		
No dim function	✗		
Dimming depending on control gear	✓		
Light distributor	Diffuser lens/optic/panel		
Light distribution	Symmetric		
Beam angle	> 80° - Extreme wide beam		
Colour consistency (McAdam ellipse)	SDCM4		
Light outlet	Direct		
Energy efficiency class of the light source according to EU regulation 2019/2015	C		
Energy efficiency class of the built-in lamp	Other		
Power supply energy efficiency index (EEI)	Other		
Energy efficiency class of the provided exchangeable built-in lamp	C		
Degree of protection (IP)	IP40		
Degree of protection (NEMA)	3		
Impact strength	IK08		
Protection class according to IEC 61140	II		
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24	✗		
Emergency power supply integrated	✗		
Suitable for emergency lighting	✗		
With movement sensor	✗		
With light sensor	✗		
Covering of the luminaire with thermally insulating material possible	✗		
With air slots	✗		
Filament test according to IEC 60695-2-11	650 °C - 30 s		
Colour of light according to EN 12464-1	Neutral white 3300-5300 K		
Colour of light	White		
Colour rendering index CRI	80-89		
Constant light output (CLO)	✗		
Type of wiring	Ending		
Connection type	Push-in clamp		
Photobiological safety according to EN 62471	RG1		
Colour of light adjustable	Positions		

LED Pro-Ceiling

PAGINA 3/3

LED Pro-Ceiling ø 240 mm (přisazené)

40001725

EAN: 8721063000081

VLASTNOSTI PRODUKTU

(Pokračování)

Luminous flux adjustable	Positions
Beam angle adjustable	No
Operation by Bluetooth	✗
Compatible with Casambi	✗
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Compatible with Amazon Alexa	✗
IFTTT support available	✗
Meets min. EIA lifetime criterion L90 (at 50,000 hours at tq = 25 °C)	✗