

## LED Pro-Space

STR. 1/2


LED Pro-Space 125 mm kruh

# 40004226

EAN: 8720604742909

### ZAŽIJTE NADČASOVOU MINIMALISTICKOU ELEGANCÍ S BEZOKRAJOVÝMI SVÍTIDLY PRO-SPACE

LED Pro-Space je elegantní a nadčasové zapuštěné svítidlo s velmi nízkou hloubkou instalace. Díky bezrámečkové konstrukci se bezproblémově integruje do jakéhokoli stropu a jeho stupeň krytí IP66 umožňuje instalaci do vlhkého prostředí.



## VLASTNOSTI PRODUKTU

|                                                |                                         |                                                      |                        |
|------------------------------------------------|-----------------------------------------|------------------------------------------------------|------------------------|
| Suitable for wall mounting                     | ✓                                       | Nominal voltage                                      | 220 240 Volt           |
| Suitable for wall mounting                     | ✓                                       | Nominal current                                      | 500 500 Milliampere    |
| Suitable for suspended mounting                | ✗                                       | Rated lifetime L70/B50 at 25 °C                      | 50000 Hour             |
| Suitable for ceiling mounting                  | ✓                                       | Rated ambient temperature according to IEC 62722-2-1 | -20 50 Degrees celsius |
| Suitable for built-in mounting                 | ✓                                       | Luminaire efficacy                                   | 76,5 Lumen/Watt        |
| Suitable for surface mounting                  | ✗                                       | Rated luminous flux according to IEC 62722-2-1       | 840 Lumen              |
| Suitable for light line configuration          | ✗                                       | Max. system power                                    | 11 Watt                |
| Suitable for workplace according to EN 12464-1 | ✗                                       | Colour temperature                                   | 4200 4200 Kelvin       |
| Lamp type                                      | LED not exchangeable                    | Power factor                                         | 0,9                    |
| With light source                              | ✓                                       | Height/depth                                         | 20 Millimetre          |
| Lamp holder                                    | Other                                   | Outer diameter                                       | 125 Millimetre         |
| Housing material                               | Aluminium                               | Built-in height/depth                                | 20 Millimetre          |
| Surface protection housing                     | Other                                   | Built-in diameter                                    | 105 Millimetre         |
| Housing colour                                 | White                                   | Unified Glare Ratio (UGR)                            | 24                     |
| Material cover                                 | Plastic, opal                           |                                                      |                        |
| Type of grid                                   | None                                    |                                                      |                        |
| Voltage type                                   | AC                                      |                                                      |                        |
| Type of control gear                           | LED operating device current-controlled |                                                      |                        |
| With control gear                              | ✓                                       |                                                      |                        |
| Dimming 0-10 V                                 | ✗                                       |                                                      |                        |
| Dimming 1-10 V                                 | ✗                                       |                                                      |                        |
| Dimming DALI                                   | ✗                                       |                                                      |                        |
| Dimming DMX                                    | ✗                                       |                                                      |                        |
| Dimming GPRS                                   | ✗                                       |                                                      |                        |
| Dimming LineSwitch                             | ✗                                       |                                                      |                        |
| Dimming DSI                                    | ✗                                       |                                                      |                        |
| Dimming manufacturer's proprietary system      | ✗                                       |                                                      |                        |
| Dimming mains voltage modulation               | ✗                                       |                                                      |                        |

## LED Pro-Space

PAGINA 2/2

LED Pro-Space 125 mm kruh

# 40004226

EAN: 8720604742909

### VLASTNOSTI PRODUKTU

(Pokračování)

|                                                                       |                           |
|-----------------------------------------------------------------------|---------------------------|
| Dimming phase cut-off (trailing edge)                                 | ✓                         |
| Dimming phase cut-on (leading edge)                                   | ✗                         |
| Dimming programmable                                                  | ✗                         |
| Dimming potentiometer (integrated)                                    | ✗                         |
| Dimming RF                                                            | ✗                         |
| Dimming Sine Wave Reduction                                           | ✗                         |
| Dimming Touch and Dim                                                 | ✗                         |
| Dimming Zigbee                                                        | ✗                         |
| Dimming with push-button                                              | ✗                         |
| No dim function                                                       | ✗                         |
| Dimming depending on control gear                                     | ✓                         |
| Light distributor                                                     | Diffuser lens/optic/panel |
| Light distribution                                                    | Symmetric                 |
| Beam angle                                                            | > 80° - Extreme wide beam |
| Colour consistency (McAdam ellipse)                                   | SDCM4                     |
| Light outlet                                                          | Direct                    |
| Energy efficiency class of the built-in lamp                          | A++, A+, A (LED)          |
| Degree of protection (IP)                                             | IP66                      |
| Impact strength                                                       | IK08                      |
| Protection class according to IEC 61140                               | II                        |
| Emergency power supply integrated                                     | ✗                         |
| Suitable for emergency lighting                                       | ✗                         |
| With movement sensor                                                  | ✗                         |
| With light sensor                                                     | ✗                         |
| Covering of the luminaire with thermally insulating material possible | ✗                         |
| With air slots                                                        | ✗                         |
| Colour of light according to EN 12464-1                               | Neutral white 3300-5300 K |
| Colour of light                                                       | White                     |
| Colour rendering index CRI                                            | 80-89                     |
| Type of wiring                                                        | Ending                    |
| Connection type                                                       | Screwed terminal          |
| Operation by Bluetooth                                                | ✗                         |