

## LED Rockdisc II

STR. 1/2


LED Rockdisc II Mini ø 265 mm

# 40009016

EAN: 8719325161007

### ROBUSTNÍ A STYLOVÉ

Moderní, vodotěsné osvětlení pro vnitřní i venkovní aplikace. Volitelně k dispozici s nouzovou funkcí a novým mikrovlnným senzorem: 3-stupňové stmívání, funkce zap. / vyp. na základě denního osvětlení, rozsah detekce, doba osvětlení a nastavení citlivosti denního světla. Kromě toho mohou být přístroje s čidlem a bez něj kombinovány jako master / slave.



### VLASTNOSTI PRODUKTU

|                                                |                                         |                                                                           |                          |
|------------------------------------------------|-----------------------------------------|---------------------------------------------------------------------------|--------------------------|
| Suitable for wall mounting                     | ✓                                       | Nominal voltage                                                           | 220   240 Volt           |
| Suitable for wall mounting                     | ✓                                       | Rated lifetime L70/B50 at 25 °C                                           | 175000 Hour              |
| Suitable for suspended mounting                | ✗                                       | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) | 90 Percentage            |
| Suitable for ceiling mounting                  | ✓                                       | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)      | 50 Percentage            |
| Suitable for built-in mounting                 | ✗                                       | Rated life time L90/B50 at 25 °C                                          | 50000 Hour               |
| Suitable for surface mounting                  | ✓                                       | Max. number of luminaires per miniature circuit breaker B16 (MCB)         | 96                       |
| Suitable for light line configuration          | ✗                                       | Max. number of luminaires per miniature circuit breaker C16 (MCB)         | 192                      |
| Suitable for workplace according to EN 12464-1 | ✗                                       | Rated ambient temperature according to IEC 62722-2-1                      | -20   50 Degrees celsius |
| Lamp type                                      | LED exchangeable                        | Luminaire efficacy                                                        | 80 Lumen/Watt            |
| With light source                              | ✓                                       | Rated luminous flux according to IEC 62722-2-1                            | 800 Lumen                |
| Lamp holder                                    | Other                                   | Max. system power                                                         | 10 Watt                  |
| Housing material                               | Aluminium                               | Colour temperature                                                        | 4000   4000 Kelvin       |
| Surface protection housing                     | Lacquered                               | Power factor                                                              | 0,9                      |
| Housing colour                                 | Grey                                    | Height/depth                                                              | 90 Millimetre            |
| Material cover                                 | Plastic, opal                           | Outer diameter                                                            | 265 Millimetre           |
| Type of grid                                   | None                                    | Number of poles                                                           | 3                        |
| Voltage type                                   | AC                                      | Unified Glare Ratio (UGR)                                                 | 20                       |
| Type of control gear                           | LED operating device current-controlled |                                                                           |                          |
| With control gear                              | ✓                                       |                                                                           |                          |
| Dimming 0-10 V                                 | ✗                                       |                                                                           |                          |
| Dimming 1-10 V                                 | ✗                                       |                                                                           |                          |
| Dimming DALI                                   | ✗                                       |                                                                           |                          |
| Dimming DALI-2                                 | ✗                                       |                                                                           |                          |
| Dimming DMX                                    | ✗                                       |                                                                           |                          |
| Dimming GPRS                                   | ✗                                       |                                                                           |                          |
| Dimming LineSwitch                             | ✗                                       |                                                                           |                          |

## LED Rockdisc II

LED Rockdisc II Mini ø 265 mm

# 40009016

EAN: 8719325161007

### VLASTNOSTI PRODUKTU

(Pokračování)

|                                                                       |                           |
|-----------------------------------------------------------------------|---------------------------|
| Dimming DSI                                                           | ✗                         |
| Dimming manufacturer's proprietary system                             | ✗                         |
| Dimming mains voltage modulation                                      | ✗                         |
| Dimming phase cut-off (trailing edge)                                 | ✗                         |
| Dimming phase cut-on (leading edge)                                   | ✗                         |
| Dimming programmable                                                  | ✗                         |
| Dimming potentiometer (integrated)                                    | ✗                         |
| Dimming RF                                                            | ✗                         |
| Dimming Sine Wave Reduction                                           | ✗                         |
| Dimming Touch and Dim                                                 | ✗                         |
| Dimming Zigbee                                                        | ✗                         |
| Dimming with push-button                                              | ✗                         |
| No dim function                                                       | ✓                         |
| Dimming depending on control gear                                     | ✗                         |
| Light distributor                                                     | Diffuser lens/optic/panel |
| Light distribution                                                    | Symmetric                 |
| Beam angle                                                            | > 80° - Extreme wide beam |
| Colour consistency (McAdam ellipse)                                   | SDCM3                     |
| Light outlet                                                          | Direct                    |
| Containing product according to 2019/2020/EU                          | ✓                         |
| Energy efficiency class of the built-in lamp                          | A++, A+, A (LED)          |
| Degree of protection (IP)                                             | IP65                      |
| Impact strength                                                       | IK10                      |
| Protection class according to IEC 61140                               | I                         |
| Emergency power supply integrated                                     | ✗                         |
| Suitable for emergency lighting                                       | ✗                         |
| With movement sensor                                                  | ✓                         |
| With light sensor                                                     | ✗                         |
| Covering of the luminaire with thermally insulating material possible | ✗                         |
| With air slots                                                        | ✗                         |
| Filament test according to IEC 60695-2-11                             | 650 °C - 30 s             |
| Colour of light according to EN 12464-1                               | Neutral white 3300-5300 K |
| Colour of light                                                       | White                     |
| Colour rendering index CRI                                            | 80-89                     |
| Type of wiring                                                        | Ending                    |
| Connection type                                                       | Push-in clamp             |
| Colour of light adjustable                                            | No                        |
| Luminous flux adjustable                                              | No                        |
| Beam angle adjustable                                                 | No                        |
| Operation by Bluetooth                                                | ✗                         |
| Compatible with Apple HomeKit                                         | ✗                         |
| Compatible with Google Assistant                                      | ✗                         |
| Compatible with Amazon Alexa                                          | ✗                         |
| IFTTT support available                                               | ✗                         |