

LED Rockdisc II

STR. 1/2


LED Rockdisc II Mini ø 265 mm

40009240

EAN: 8720615507726

ROBUSTNÍ A STYLOVÉ

Moderní, vodotěsné osvětlení pro vnitřní i venkovní aplikace. Volitelně k dispozici s nouzovou funkcí a novým mikrovlnným senzorem: 3-stupňové stmívání, funkce zap. / vyp. na základě denního osvětlení, rozsah detekce, doba osvětlení a nastavení citlivosti denního světla. Kromě toho mohou být přístroje s čidlem a bez něj kombinovány jako master / slave.



VLASTNOSTI PRODUKTU

Suitable for wall mounting	✓	Nominal voltage	220 240 Volt
Suitable for wall mounting	✓	Rated lifetime L70/B50 at 25 °C	175000 Hour
Suitable for suspended mounting	✗	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	90 Percentage
Suitable for ceiling mounting	✗	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	50 Percentage
Suitable for built-in mounting	✗	Rated life time L90/B50 at 25 °C	50000 Hour
Suitable for surface mounting	✓	Max. number of luminaires per miniature circuit breaker B16 (MCB)	56
Suitable for light line configuration	✗	Max. number of luminaires per miniature circuit breaker C16 (MCB)	113
Suitable for workplace according to EN 12464-1	✗	Rated ambient temperature according to IEC 62722-2-1	-20 50 Degrees celsius
Lamp type	LED exchangeable	Luminaire efficacy	76,5 Lumen/Watt
With light source	✓	Rated luminous flux according to IEC 62722-2-1	1300 Lumen
Lamp holder	Other	Max. system power	17 Watt
Housing material	Aluminium	Colour temperature	3000 3000 Kelvin
Surface protection housing	Lacquered	Power factor	0,9
Housing colour	Grey	Height/depth	105 Millimetre
Material cover	Plastic, opal	Outer diameter	360 Millimetre
Type of grid	None	Number of poles	3
Voltage type	AC	Unified Glare Ratio (UGR)	20
Type of control gear	LED operating device current-controlled		
With control gear	✓		
Dimming 0-10 V	✗		
Dimming 1-10 V	✗		
Dimming DALI	✗		
Dimming DALI-2	✗		
Dimming DMX	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		

LED Rockdisc II

PAGINA 2/2

LED Rockdisc II Mini ø 265 mm

40009240

EAN: 8720615507726

VLASTNOSTI PRODUKTU

(Pokračování)

Dimming DSI	✗
Dimming manufacturer's proprietary system	✗
Dimming mains voltage modulation	✗
Dimming phase cut-off (trailing edge)	✗
Dimming phase cut-on (leading edge)	✗
Dimming programmable	✗
Dimming potentiometer (integrated)	✗
Dimming RF	✗
Dimming Sine Wave Reduction	✗
Dimming Touch and Dim	✗
Dimming Zigbee	✗
Dimming with push-button	✗
No dim function	✓
Dimming depending on control gear	✗
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Containing product according to 2019/2020/EU	✓
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP65
Impact strength	IK10
Protection class according to IEC 61140	I
Emergency power supply integrated	✗
Suitable for emergency lighting	✗
With movement sensor	✗
With light sensor	✓
Covering of the luminaire with thermally insulating material possible	✗
With air slots	✗
Filament test according to IEC 60695-2-11	650 °C - 30 s
Colour of light according to EN 12464-1	Warm white < 3300 K
Colour of light	White
Colour rendering index CRI	80-89
Type of wiring	Ending
Connection type	Push-in clamp
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No
Operation by Bluetooth	✗
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Compatible with Amazon Alexa	✗
IFTTT support available	✗