

LED Prodisc II IP65

STR. 1/2


LED Prodisc II IP65 + čidlo denního osvětlení

40009854

EAN: 8720604744026

VODOTĚSNÝ A UNIVERZÁLNÍ

Prodisc II IP65 je voděodolná verze populárního svítidla Prodisc II značky Prolumia. Toto úsporné a výkonné svítidlo je vhodné k venkovnímu použití, a to i v náročných povětrnostních podmínkách. Skvělé pro veřejné budovy, podchody, chodby, schodiště, skladiště, terasy apod. Díky své variabilitě se stalo svítidlo Prodisc II univerzálním pro mnoho použití.



VLASTNOSTI PRODUKTU

Suitable for wall mounting	✓	Nominal voltage	220 240 Volt
Suitable for wall mounting	✓	Rated lifetime L70/B50 at 25 °C	175000 Hour
Suitable for suspended mounting	✗	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	90 Percentage
Suitable for ceiling mounting	✓	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq)	50 Percentage
Suitable for built-in mounting	✗	Rated life time L80/B10 at 25 °C	10000 Hour
Suitable for surface mounting	✓	Rated life time L90/B50 at 25 °C	50000 Hour
Suitable for light line configuration	✗	Rated ambient temperature according to IEC 62722-2-1	-20 50 Degrees celsius
Suitable for workplace according to EN 12464-1	✗	Luminaire efficacy	107 Lumen/Watt
Lamp type	LED not exchangeable	Rated luminous flux according to IEC 62722-2-1	1500 Lumen
With light source	✓	Max. system power	14 Watt
Lamp holder	Other	Colour temperature	3000 4000 Kelvin
Housing material	Plastic	Power factor	0,9
Surface protection housing	Other	Height/depth	100 Millimetre
Housing colour	White	Outer diameter	370 Millimetre
Material cover	Plastic, opal	Number of poles	2
Type of grid	None		
Voltage type	AC		
Type of control gear	LED operating device current-controlled		
With control gear	✓		
Exchangeable control gear	✗		
Dimming 0-10 V	✗		
Dimming 1-10 V	✗		
Dimming DALI	✗		
Dimming DALI-2	✗		
Dimming DMX	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		

LED Prodisc II IP65

LED Prodisc II IP65 + čidlo denního osvětlení

40009854

EAN: 8720604744026

VLASTNOSTI PRODUKTU

(Pokračování)

Dimming DSI	✘
Dimming manufacturer's proprietary system	✘
Dimming mains voltage modulation	✘
Dimming phase cut-off (trailing edge)	✘
Dimming phase cut-on (leading edge)	✘
Dimming programmable	✘
Dimming potentiometer (integrated)	✘
Dimming RF	✘
Dimming Sine Wave Reduction	✘
Dimming Touch and Dim	✘
Dimming Zigbee	✘
Dimming with push-button	✘
No dim function	✓
Dimming depending on control gear	✘
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP65
Impact strength	IK10
Protection class according to IEC 61140	II
Emergency power supply integrated	✘
Suitable for emergency lighting	✘
With movement sensor	✘
With light sensor	✘
Covering of the luminaire with thermally insulating material possible	✘
With air slots	✘
Colour of light according to EN 12464-1	Neutral white 3300-5300 K
Colour of light	White
Colour rendering index CRI	80-89
Type of wiring	Ending
Connection type	Push-in clamp
Colour of light adjustable	Positions
Beam angle adjustable	No
Operation by Bluetooth	✘
Compatible with Apple HomeKit	✘
Compatible with Google Assistant	✘
Compatible with Amazon Alexa	✘
IFTTT support available	✘