

## LED Pro-Fit

STR. 1/2


LED Pro-Fit černé s krytem

# 40010331

EAN: 8720604744347

## ROBUSTNÍ A RETROSTYLOVÁ STROPNÍ A NÁSTĚNNÁ SVÍTLIDLA S MOŽNOSTMI ÚSPORY ENERGIE

Řada Pro-Fit se skládá ze dvou typů robustních stropních a nástěnných svítidel. Jsou vhodná nejen pro bytovou výstavbu, pro použití nad vchody, v chodbách, galeriích a skladech, ale také k montáži na fasádě budov. Jedná se o skvělou 1-ku-1 náhradu za nejčastěji používaná konvenční svítidla, kde Vám odpovídající rozměry ušetří malování.



### VLASTNOSTI PRODUKTU

|                                           |                                         |                                 |                       |
|-------------------------------------------|-----------------------------------------|---------------------------------|-----------------------|
| Suitable for wall mounting                | ✓                                       | Nominal voltage                 | 240   240 Volt        |
| Suitable for wall mounting                | ✓                                       | Rated lifetime L70/B50 at 25 °C | 100000 Hour           |
| Suitable for suspended mounting           | ✗                                       | Luminaire efficacy              | 100 Lumen/Watt        |
| Suitable for ceiling mounting             | ✓                                       | Max. system power               | 7 Watt                |
| Suitable for built-in mounting            | ✗                                       | Colour temperature              | 3000   4000 Kelvin    |
| Suitable for surface mounting             | ✓                                       | Power factor                    | 0,8                   |
| Suitable for light line configuration     | ✗                                       | Width                           | 140 Millimetre        |
| Lamp type                                 | LED exchangeable                        | Height/depth                    | 110 Millimetre        |
| With light source                         | ✓                                       | Length                          | 280 Millimetre        |
| Lamp holder                               | Other                                   | Number of poles                 | 2                     |
| Housing material                          | Plastic                                 | Conductor cross section         | 1,5 Square millimetre |
| Surface protection housing                | Untreated                               |                                 |                       |
| Housing colour                            | Black                                   |                                 |                       |
| Material cover                            | Plastic, transparent                    |                                 |                       |
| Type of grid                              | None                                    |                                 |                       |
| Voltage type                              | AC                                      |                                 |                       |
| Type of control gear                      | LED operating device current-controlled |                                 |                       |
| With control gear                         | ✓                                       |                                 |                       |
| Exchangeable control gear                 | ✗                                       |                                 |                       |
| Dimming 0-10 V                            | ✗                                       |                                 |                       |
| Dimming 1-10 V                            | ✗                                       |                                 |                       |
| Dimming DALI                              | ✗                                       |                                 |                       |
| Dimming DALI-2                            | ✗                                       |                                 |                       |
| Dimming DMX                               | ✗                                       |                                 |                       |
| Dimming GPRS                              | ✗                                       |                                 |                       |
| Dimming LineSwitch                        | ✗                                       |                                 |                       |
| Dimming DSI                               | ✗                                       |                                 |                       |
| Dimming manufacturer's proprietary system | ✗                                       |                                 |                       |
| Dimming mains voltage modulation          | ✗                                       |                                 |                       |
| Dimming phase cut-off (trailing edge)     | ✗                                       |                                 |                       |

## LED Pro-Fit

PAGINA 2/2

LED Pro-Fit černé s krytem

# 40010331

EAN: 8720604744347

### VLASTNOSTI PRODUKTU

(Pokračování)

|                                                                       |                           |
|-----------------------------------------------------------------------|---------------------------|
| Dimming phase cut-on (leading edge)                                   | ✗                         |
| Dimming programmable                                                  | ✗                         |
| Dimming potentiometer (integrated)                                    | ✗                         |
| Dimming RF                                                            | ✗                         |
| Dimming Sine Wave Reduction                                           | ✗                         |
| Dimming Touch and Dim                                                 | ✗                         |
| Dimming Zigbee                                                        | ✗                         |
| Dimming with push-button                                              | ✗                         |
| No dim function                                                       | ✓                         |
| Dimming depending on control gear                                     | ✗                         |
| Light distributor                                                     | Other                     |
| Light distribution                                                    | Symmetric                 |
| Beam angle                                                            | > 80° - Extreme wide beam |
| Colour consistency (McAdam ellipse)                                   | SDCM3                     |
| Light outlet                                                          | Direct                    |
| Containing product according to 2019/2020/EU                          | ✓                         |
| Energy efficiency class of the built-in lamp                          | A++, A+, A (LED)          |
| Degree of protection (IP)                                             | IP66                      |
| Impact strength                                                       | IK10                      |
| Protection class according to IEC 61140                               | II                        |
| Emergency power supply integrated                                     | ✗                         |
| Suitable for emergency lighting                                       | ✗                         |
| With movement sensor                                                  | ✓                         |
| With light sensor                                                     | ✗                         |
| Covering of the luminaire with thermally insulating material possible | ✓                         |
| With air slots                                                        | ✗                         |
| Filament test according to IEC 60695-2-11                             | 650 °C - 30 s             |
| Colour of light                                                       | White                     |
| Colour rendering index CRI                                            | 80-89                     |
| Type of wiring                                                        | Ending                    |
| Connection type                                                       | Push-in clamp             |
| Operation by Bluetooth                                                | ✗                         |
| Compatible with Apple HomeKit                                         | ✗                         |
| Compatible with Google Assistant                                      | ✗                         |
| Compatible with Amazon Alexa                                          | ✗                         |
| IFTTT support available                                               | ✗                         |