

LED Pro-Line Retrofit II

STR. 1/2


LED Pro-Line Retrofit II modul

40640404

EAN: 8720604745641

UNIVERZÁLNÍ NÁHRADA ZA JEDNO- A DVOJ-TRUBICOVÁ ZÁŘIVKOVÁ SVÍTIDLA T5 A T8

Řada svítidel LED Pro-Line Retrofit s moduly standardně stmívatelnými 1-10V jsou univerzální náhradou za jedno- a dvoj-trubicová zářivková svítidla a jsou vhodná k použití s většinou stávajících systémů. Se zachováním stávajících úchytů a závěsů světelných modulů zajišťuje Retrofit kompletní nové a velmi účinné osvětlení, a to hlavně díky průběžné montáži.



VLASTNOSTI PRODUKTU

Suitable for light line configuration	✓	Nominal voltage	220 240 Volt
Suitable for workplace according to EN 12464-1	✗	Rated lifetime L70/B50 at 25 °C	78000 Hour
Lamp type	LED not exchangeable	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq)	85 Percentage
With light source	✓	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 Percentage
Lamp holder	Other	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq)	70 Percentage
Housing material	Aluminium	Rated life time L80/B10 at 25 °C	42000 Hour
Surface protection housing	Other	Rated life time L90/B10 at 25 °C	21000 Hour
Housing colour	Aluminium	Rated life time L90/B50 at 25 °C	24000 Hour
Material cover	Plastic, opal	Rated ambient temperature according to IEC 62722-2-1	-25 45 Degrees celsius
Type of grid	None	Luminaire efficacy	142 Lumen/Watt
Voltage type	AC	Rated luminous flux according to IEC 62722-2-1	10680 Lumen
Type of control gear	LED operating device current-controlled	Max. system power	75 Watt
With control gear	✓	Colour temperature	4000 4000 Kelvin
Dimming 0-10 V	✗	Length	1527 Millimetre
Dimming 1-10 V	✓	Number of poles	8
Dimming DALI	✗		
Dimming DALI-2	✗		
Dimming DMX	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		
Dimming DSI	✗		
Dimming manufacturer's proprietary system	✗		
Dimming mains voltage modulation	✗		
Dimming phase cut-off (trailing edge)	✗		
Dimming phase cut-on (leading edge)	✗		
Dimming programmable	✗		

LED Pro-Line Retrofit II

PAGINA 2/2

LED Pro-Line Retrofit II modul

40640404

EAN: 8720604745641

VLASTNOSTI PRODUKTU

(Pokračování)

Dimming potentiometer (integrated)	✗
Dimming RF	✗
Dimming Sine Wave Reduction	✗
Dimming Touch and Dim	✗
Dimming Zigbee	✗
Dimming with push-button	✗
No dim function	✗
Dimming depending on control gear	✗
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP40
Degree of protection (NEMA)	3
Impact strength	IK08
Protection class according to IEC 61140	I
Emergency power supply integrated	✗
Suitable for emergency lighting	✓
With movement sensor	✗
With light sensor	✗
Covering of the luminaire with thermally insulating material possible	✓
With air slots	✗
Colour of light	White
Colour rendering index CRI	80-89
Type of wiring	Loop-through wiring included
Connection type	Plug
Luminous flux adjustable	Positions
Beam angle adjustable	No