

LED Pro-Flood

STR. 1/1


LED Pro-Flood 50W

41060740

EAN: 8720604748475

SKVĚLÝ VÝKON V KOMPAKTNÍM PROVEDENÍ

Robustní řada svítidel Prolumia Pro-Flood se skládá z funkčních a kompaktně navržených bodových světel v pěti různých rozměrech pro vnitřní i venkovní použití. K dispozici se symetrickou a asymetrickou optikou. Ideálně se hodí mimo jiné k osvětlení obchodních ploch, parkovišť, sportovních hřišť a fasád.



VLASTNOSTI PRODUKTU

Suitable for surface mounting	✓	Suitable for number of light sources	1
Suitable for built-in mounting	✗	Nominal voltage	220 240 Volt
Suitable for wall mounting	✓	Rated ambient temperature according to IEC 62722-2-1	-30 50 Degrees celsius
Suitable for wall mounting	✓	Max. system power	50 Watt
Suitable for suspended mounting	✗	Luminous flux	5900 5900 Lumen
Suitable for ceiling mounting	✓	Colour temperature	3000 3000 Kelvin
Suitable for traverse mounting	✓	Length	55 Millimetre
Suitable for pedestal/floor mounting	✓	Width	228 Millimetre
Suitable for light-track mounting	✗	Height/depth	267 Millimetre
Suitable for clamp-mounting	✓		
Adjustability	Rotatable		
With movement sensor	✗		
With light sensor	✗		
Lamp type	LED not exchangeable		
With light source	✓		
Lamp holder	Other		
Housing material	Aluminium		
Surface protection	Powder coating		
Housing colour	Black		
Material cover	Glass transparent		
Surface brushed	✗		
Voltage type	AC		
Type of control gear	LED operating device current-controlled		
With control gear	✓		
No dim function	✓		
Reflector	None		
Light distribution	Asymmetric		
Light outlet	Direct		
Degree of protection (IP)	IP66		
Protection class according to IEC 61140	I		
Colour of light	White		