

LED Pro-Rio Tracklight

STR. 1/2


LED Pro-Rio Tracklight D

41104540

EAN: 8720615501670

FLEXIBILNÍ ŘEŠENÍ OSVĚTLENÍ, KTERÉ ROZZÁŘÍ BARVY

Série LED svítidel Pro-Rio Tracklight obsahuje řadu elegantních bodových svítidel, která jsou vhodná zejména pro použití v obchodech, muzeích a galeriích. S tímto LED osvětlením můžete optimálně nasvětlit Vaše výrobky a další objekty, které tak skvěle vyniknou. Díky vysoké hodnotě Ra máte jistotu reprodukce přirozených barev. Doplněte tato svítidla o 3-fázovou lištu, a tím získáte nekonečné možnosti jejich polohování a rozmístění.



VLASTNOSTI PRODUKTU

Suitable for surface mounting	✓	Nominal voltage	220 240 Volt
Suitable for built-in mounting	✗	Rated lifetime L70/B50 at 25 °C	50000 Hour
Suitable for wall mounting	✓	Rated ambient temperature according to IEC 62722-2-1	-5 35 Degrees celsius
Suitable for wall mounting	✓	Max. system power	26 Watt
Suitable for suspended mounting	✗	Luminous flux	2600 2600 Lumen
Suitable for ceiling mounting	✓	Rated luminous flux according to IEC 62722-2-1	2600 Lumen
Suitable for traverse mounting	✗	Lamp efficacy	100 Lumen/Watt
Suitable for pedestal/floor mounting	✗	Colour temperature	3000 3000 Kelvin
Suitable for light-track mounting	✓	Power factor	0,9
Suitable for clamp-mounting	✗	Length	162 Millimetre
Suitable for low voltage cable system	✗	Height/depth	121 Millimetre
Adjustability	Rotatable	Outer diameter	85 Millimetre
With movement sensor	✗	Number of poles	3
With light sensor	✗	Luminaire efficacy	100 Lumen/Watt
Lamp type	LED not exchangeable	Unified Glare Ratio (UGR)	14
With light source	✓		
Lamp holder	Other		
Housing material	Aluminium		
Housing colour	Black		
Material cover	Without cover		
Voltage type	AC		
Type of control gear	LED operating device current-controlled		
With control gear	✓		
Dimming depending on control gear	✗		
Dimming 0-10 V	✗		
Dimming 1-10 V	✗		
Dimming DALI-2	✗		
Dimming DALI	✗		
Dimming DMX	✗		
Dimming DSI	✗		

LED Pro-Rio Tracklight

PAGINA 2/2

LED Pro-Rio Tracklight D

41104540

EAN: 8720615501670

VLASTNOSTI PRODUKTU

(Pokračování)

Dimming GPRS	✗
Dimming potentiometer (integrated)	✗
Dimming LineSwitch	✗
Dimming manufacturer's proprietary system	✗
Dimming mains voltage modulation	✗
Dimming phase cut-off (trailing edge)	✗
Dimming phase cut-on (leading edge)	✗
Dimming programmable	✗
Dimming RF	✗
Dimming Sine Wave Reduction	✗
Dimming Touch and Dim	✗
Dimming Zigbee	✗
No dim function	✓
Dimming with push-button	✗
Light distributor	Reflector
Light distribution	Symmetric
Beam angle	21-40° - Medium beam
Light outlet	Direct
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP20
Protection class according to IEC 61140	I
Colour of light	White
Colour of light adjustable	No
Colour rendering index CRI	90-100
Luminous flux adjustable	No
Beam angle adjustable	No
Type of wiring	Ending
Emergency power supply integrated	✗
Connection type	Other
Suitable for workplace according to EN 12464-1	✗
Covering of the luminaire with thermally insulating material possible	✗
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Compatible with Amazon Alexa	✗