


LED Pro-Strada Mini

41361300

EAN:

FUNKČNOST BEZ KOMPROMISŮ. PŘIPRAVENO NA BUDOUCNOST.

Svítilno LED Pro-Strada je naprosto všestranné. Toto svítidlo dokáže skloubit účinnost se světelným komfortem. To vše spolu se širokou škálou výkonnostních variant, verzích upravených pro individuální použití a standardně vybaveno zásuvkou Zhaga. Díky tomu je řada těchto svítidel bezpečná a jasná volba pro Vaši budoucnost.



VLASTNOSTI PRODUKTU

Mounting method	Post top/side entry	Suitable for number of light sources	1
Lamp type	LED not exchangeable	Nominal voltage	220 240 Volt
With light source	✓	Nominal current	355 355 Milliampere
Lamp holder	Other	Rated life time L80/B10 at 25 °C	100000 Hour
Housing material	Aluminium	Rated ambient temperature according to IEC 62722-2-1	-30 50 Degrees celsius
Surface protection	Powder coating	Cable length	1 Metre
Housing colour	Grey	Rated luminous flux according to IEC 62722-2-1	2600 Lumen
Material cover	Glass transparent	Max. system power	24 Watt
Voltage type	AC	Luminaire efficacy	108,5 Lumen/Watt
With control gear	✓	Colour temperature	3000 3000 Kelvin
Type of control gear	LED operating device current-controlled	Power factor	0,9
Exchangeable control gear	✓	Width	307 Millimetre
Dimming 0-10 V	✓	Height/depth	108 Millimetre
Dimming 1-10 V	✓	Length	697 Millimetre
Dimming GPRS	✗	Suitable for spigot size	60 60 Millimetre
Dimming DALI	✓	Number of poles	3
Dimming DMX	✗	Conductor cross section	1,5 Square millimetre
Dimming DSI	✗		
Dimming potentiometer (integrated)	✗		
Dimming LineSwitch	✗		
Dimming manufacturer's proprietary system	✗		
Dimming mains voltage modulation	✗		
Dimming phase cut-off (trailing edge)	✗		
Dimming phase cut-on (leading edge)	✗		
Dimming Touch and Dim	✗		
Dimming programmable	✓		
Dimming with push-button	✗		
No dim function	✗		
Dimming RF	✗		
Dimming Sine Wave Reduction	✗		
Dimming Zigbee	✗		
Light distributor	Focal lens		
Energy efficiency class of the built-in lamp	A++, A+, A (LED)		

LED Pro-Strada

LED Pro-Strada Mini

41361300

EAN:

VLASTNOSTI PRODUKTU

(Pokračování)

Adjustable optics	✘
Colour consistency (McAdam ellipse)	SDCM3
Degree of protection (IP)	IP66
Impact strength	IK09
Protection class according to IEC 61140	II
With radio control	✘
Constant light output (CLO)	✘
With light regulation program control	✓
With connection cable	✓
Colour of light	White
Colour rendering index CRI	70-79
Type of wiring	Ending
Compatible with Apple HomeKit	✘
Compatible with Google Assistant	✘
Connection type	Screwed terminal
Compatible with Amazon Alexa	✘
IFTTT support available	✘
Operation by Bluetooth	✘