

## LED Pro-Strada

STR. 1/2

LED Pro-Strada Micro

# 41369150

EAN:

### FUNKČNOST BEZ KOMPROMISŮ. PŘIPRAVENO NA BUDOUCNOST.

Svítlidlo LED Pro-Strada je naprosto všestranné. Toto svítidlo dokáže skloubit účinnost se světelným komfortem. To vše spolu se širokou škálou výkonnostních variant, verzích upravených pro individuální použití a standardně vybaveno zásuvkou Zhaga. Díky tomu je řada těchto svítidel bezpečná a jasná volba pro Vaši budoucnost.



### VLASTNOSTI PRODUKTU

|                                              |                                         |                                                      |                        |
|----------------------------------------------|-----------------------------------------|------------------------------------------------------|------------------------|
| Mounting method                              | Post top/side entry                     | Suitable for number of light sources                 | 1                      |
| Lamp type                                    | LED not exchangeable                    | Nominal voltage                                      | 220 240 Volt           |
| With light source                            | ✓                                       | Nominal current                                      | 140 140 Milliampere    |
| Lamp holder                                  | Other                                   | Rated life time L80/B10 at 25 °C                     | 100000 Hour            |
| Housing material                             | Aluminium                               | Rated ambient temperature according to IEC 62722-2-1 | -30 50 Degrees celsius |
| Surface protection                           | Powder coating                          | Cable length                                         | 1 Metre                |
| Housing colour                               | Grey                                    | Rated luminous flux according to IEC 62722-2-1       | 800 Lumen              |
| Material cover                               | Glass transparent                       | Max. system power                                    | 7 Watt                 |
| Voltage type                                 | AC                                      | Luminaire efficacy                                   | 114,5 Lumen/Watt       |
| With control gear                            | ✓                                       | Colour temperature                                   | 3000 3000 Kelvin       |
| Type of control gear                         | LED operating device current-controlled | Power factor                                         | 0,9                    |
| Exchangeable control gear                    | ✓                                       | Width                                                | 229 Millimetre         |
| Dimming 0-10 V                               | ✓                                       | Height/depth                                         | 114 Millimetre         |
| Dimming 1-10 V                               | ✓                                       | Length                                               | 543 Millimetre         |
| Dimming GPRS                                 | ✗                                       | Suitable for spigot size                             | 60 60 Millimetre       |
| Dimming DALI                                 | ✓                                       | Number of poles                                      | 3                      |
| Dimming DMX                                  | ✗                                       | Conductor cross section                              | 1,5 Square millimetre  |
| Dimming DSI                                  | ✗                                       |                                                      |                        |
| Dimming potentiometer (integrated)           | ✗                                       |                                                      |                        |
| Dimming LineSwitch                           | ✗                                       |                                                      |                        |
| Dimming manufacturer's proprietary system    | ✗                                       |                                                      |                        |
| Dimming mains voltage modulation             | ✗                                       |                                                      |                        |
| Dimming phase cut-off (trailing edge)        | ✗                                       |                                                      |                        |
| Dimming phase cut-on (leading edge)          | ✗                                       |                                                      |                        |
| Dimming Touch and Dim                        | ✗                                       |                                                      |                        |
| Dimming programmable                         | ✓                                       |                                                      |                        |
| Dimming with push-button                     | ✗                                       |                                                      |                        |
| No dim function                              | ✗                                       |                                                      |                        |
| Dimming RF                                   | ✗                                       |                                                      |                        |
| Dimming Sine Wave Reduction                  | ✗                                       |                                                      |                        |
| Dimming Zigbee                               | ✗                                       |                                                      |                        |
| Light distributor                            | Focal lens                              |                                                      |                        |
| Energy efficiency class of the built-in lamp | A++, A+, A (LED)                        |                                                      |                        |

## LED Pro-Strada

PAGINA 2/2

LED Pro-Strada Micro

# 41369150

EAN:

### VLASTNOSTI PRODUKTU

(Pokračování)

|                                         |                |
|-----------------------------------------|----------------|
| Adjustable optics                       | ✗              |
| Colour consistency (McAdam ellipse)     | SDCM3          |
| Degree of protection (IP)               | IP66           |
| Impact strength                         | IK09           |
| Protection class according to IEC 61140 | II             |
| With radio control                      | ✗              |
| Constant light output (CLO)             | ✗              |
| With light regulation program control   | ✓              |
| With connection cable                   | ✓              |
| Colour of light                         | White          |
| Colour rendering index CRI              | 70-79          |
| Type of wiring                          | Ending         |
| Compatible with Apple HomeKit           | ✗              |
| Compatible with Google Assistant        | ✗              |
| Connection type                         | Screw terminal |
| Compatible with Amazon Alexa            | ✗              |
| IFTTT support available                 | ✗              |
| Operation by Bluetooth                  | ✗              |