

## LED Lumiaflex II

STR. 1/1

LED Lumiaflex II

# 46000224

EAN: 8720615504015

### FLEXIBILNÍ INOVACE OSVĚTLENÍ, KTERÁ VYNIKÁ FORMOU A FUNKCÍ

Nová řada produktů LED Lumiaflex II značky Prolumia je ideální náhradou za tradiční skleněná neonová světla. Toto nerozbitné a vodotěsné lineární osvětlení je k dispozici v mnoha barevných variantách a má jednoduší světelný výkon. LED Lumiaflex II lze snadno ohnout, a proto je vhodné pro tvorbu písmen a obrázků.



### VLASTNOSTI PRODUKTU

|                                  |                                         |                                  |                        |
|----------------------------------|-----------------------------------------|----------------------------------|------------------------|
| Model                            | Hose                                    | Number of nodes per meter        | 60                     |
| Mounting method                  | Surface mounting/recessed mounting      | Lamp power per meter             | 12 Watt                |
| Lamp type                        | LED not exchangeable                    | Luminous flux per meter          | 400 Lumen              |
| Voltage type                     | DC                                      | Lamp voltage                     | 22 26 Volt             |
| Type of control gear             | LED operating device voltage-controlled | Beam angle                       | 160 Degrees            |
| Suitable for dimmer              | ✓                                       | Rated lifetime L70/B50 at 25 °C  | 50000 Hour             |
| Exchangeable control gear        | ✗                                       | Rated life time L80/B10 at 25 °C | 10 Hour                |
| Degree of protection (IP)        | IP68                                    | Max. system power                | 120 Watt               |
| Degree of protection (NEMA)      | 3                                       | Colour temperature               | 6500 6500 Kelvin       |
| Colour of light                  | White                                   | Width                            | 11,5 Millimetre        |
| Colour rendering index CRI       | 80-89                                   | Height/depth                     | 29 Millimetre          |
| With end piece                   | ✗                                       | Length                           | 10000 Millimetre       |
| With connection set              | ✗                                       | Diameter                         | 11,5 Millimetre        |
| With protective cover            | ✓                                       | Length of particular segments    | 83,3 Millimetre        |
| Self-adhesive                    | ✗                                       | Lowest bending radius            | 120 Millimetre         |
| Type of wiring                   | Ending                                  | Number of poles                  | 2                      |
| Connection type                  | Other                                   | Conductor cross section          | 0,75 Square millimetre |
| Compatible with Apple HomeKit    | ✗                                       |                                  |                        |
| Compatible with Google Assistant | ✗                                       |                                  |                        |
| Compatible with Amazon Alexa     | ✗                                       |                                  |                        |
| IFTTT support available          | ✗                                       |                                  |                        |