

LED pásek Silver

STR. 1/1


LED Strip Silver Color

46180107

EAN: 8720615504237

ODOLNÉ PROTI PRACHU A VLHKOSTI

LED pásek řady Silver je vybaven ochrannou silikonovou vrstvou, která tvoří pásek odolnější proti prachu a vlhkosti. Navzdory této průhledné vrstvě zůstává LED pásek po dlouhou dobu extrémně flexibilní, a to i při nízkých teplotách. Díky své snadné instalaci a flexibilitě je tento LED pásek architektky často využíván při osvětlení restaurací, obchodů a kanceláří.



VLASTNOSTI PRODUKTU

Model	Strip	Number of nodes per meter	60
Mounting method	Surface mounting/recessed mounting	Lamp power per meter	14,4 Watt
Lamp type	LED not exchangeable	Luminous flux per meter	540 Lumen
Voltage type	DC	Lamp voltage	24 24 Volt
Type of control gear	LED operating device voltage-controlled	Beam angle	120 Degrees
Suitable for dimmer	✓	Rated lifetime L70/B50 at 25 °C	50000 Hour
Exchangeable control gear	✗	Max. system power	72 Watt
Degree of protection (IP)	Other	Colour temperature	2400 2400 Kelvin
Degree of protection (NEMA)	2	Width	12 Millimetre
Colour of light	RGBW	Height/depth	3 Millimetre
Colour rendering index CRI	80-89	Length	5000 Millimetre
With end piece	✓	Length of particular segments	200 Millimetre
With connection set	✗	Lowest bending radius	0 Millimetre
With protective cover	✓	Number of poles	5
Self-adhesive	✗	Conductor cross section	0,75 Square millimetre
Type of wiring	Ending		
Connection type	Other		
Compatible with Apple HomeKit	✗		
Compatible with Google Assistant	✗		
Compatible with Amazon Alexa	✗		
IFTTT support available	✗		