

LED drivers

PAGE 1/1

LED I-Panel drivers

40000525

EAN: 8720615508327

PURE POWER

The different kind of LED power supplies are available for both indoor and outdoor applications (waterproof). Thanks to the relatively thin size of the power supplies, it can easily be concealed under a shelf, in a cabinet or behind a wall.

PRODUCT FEATURES

Model	Dynamic	Output voltage	36 72 Volt
Suitable for outdoor use	✗	Output current	2100 2100 Milliampere
Dimming 0-10 V	✓	Output power	150 150 Watt
Dimming 1-10 V	✗	Length	220 Millimetre
Dimming DALI	✗	Width	60 Millimetre
Dimming DMX	✗	Height	36 Millimetre
Dimming DSI	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		
Dimming mains voltage modulation	✗		
Dimming manufacturer's proprietary system	✗		
Dimming phase cut-off (trailing edge)	✗		
Dimming phase cut-on (leading edge)	✗		
Dimming potentiometer (integrated)	✗		
Dimming programmable	✗		
Dimming RF	✗		
Dimming Sine Wave Reduction	✗		
Dimming Touch and Dim	✗		
Dimming with push-button	✗		
Dimming Zigbee	✗		
No dim function	✗		
Constant light output (CLO)	✗		
Housing	Metal housing		
Suitable for constant current	✓		
Suitable for constant voltage	✗		
Suitable for DC-voltage (primary side)	✗		
Degree of protection (IP)	IP67		
Protection class according to IEC 61140	I		
Operation by Bluetooth	✗		
Compatible with Apple HomeKit	✗		
Compatible with Google Assistant	✗		
Compatible with Amazon Alexa	✗		
Compatible with Casambi	✗		
IFTTT support available	✗		