

LED I-Panel

PAGE 1/2

LED I-Panel drivers

40000533

EAN: 8720604740257

ALTERNATIVE FOR TRADITIONAL RECESSED FLUORESCENCE LUMINAIRES

The LED I-Panel series are a good alternative for traditional recessed fluorescence luminaires. The neat lines and the limited height give these series a modern and timeless character. Through the various installation options; surface mounted, recessed and suspended, the LED I-panel has a very wide field of application.



PRODUCT FEATURES

Model	Dynamic	Output voltage	3 48 Volt
Suitable for outdoor use	✗	Output current	250 700 Milliampere
Dimming 0-10 V	✗	Output power	12 32 Watt
Dimming 1-10 V	✗	Length	130 Millimetre
Dimming DALI	✓	Width	67 Millimetre
Dimming DMX	✗	Height	22 Millimetre
Dimming DSI	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		
Dimming mains voltage modulation	✗		
Dimming manufacturer's proprietary system	✗		
Dimming phase cut-off (trailing edge)	✗		
Dimming phase cut-on (leading edge)	✗		
Dimming potentiometer (integrated)	✗		
Dimming programmable	✗		
Dimming RF	✗		
Dimming Sine Wave Reduction	✗		
Dimming Touch and Dim	✗		
Dimming with push-button	✗		
Dimming Zigbee	✗		
No dim function	✗		
Constant light output (CLO)	✗		
Housing	Plastic housing		
Suitable for constant current	✓		
Suitable for constant voltage	✗		
Suitable for DC-voltage (primary side)	✗		
Degree of protection (IP)	IP20		
Protection class according to IEC 61140	II		
Operation by Bluetooth	✗		
Compatible with Apple HomeKit	✗		

LED I-Panel

LED I-Panel drivers

40000533
EAN: 8720604740257

PRODUCT FEATURES
(continuation)

Compatible with Google Assistant	✕
Compatible with Amazon Alexa	✕
Compatible with Casambi	✕
IFTTT support available	✕