

LED Pro-Ceiling

PAGE 1/2


LED Pro-Ceiling ø 240 mm (surface mount)

40001123

EAN: 8720615507450

THE WARMTH OF DECORATIVE LIGHTING COMBINED WITH A SOPHISTICATED, MODERN DESIGN

The Prolumia LED Pro-Ceiling series are unique in their design. It combines the warmth from a decorative light with the refinement of a modern, nowadays armature. Available in a round or square shape for ceiling or wall mounting The Prolumia LED Pro-Ceiling series has a lifespan of over 50.000 hours, comes complete with integrated power supply and is installed quickly and easily!



PRODUCT FEATURES

Suitable for wall mounting	✓	Nominal voltage	220 240 Volt
Suitable for wall mounting	✓	Rated ambient temperature according to IEC 62722-2-1	-10 40 Degrees celsius
Suitable for suspended mounting	✗	Luminaire efficacy	74 Lumen/Watt
Suitable for ceiling mounting	✓	Rated luminous flux according to IEC 62722-2-1	1110 Lumen
Suitable for built-in mounting	✗	Max. system power	15 Watt
Suitable for surface mounting	✓		
Suitable for light line configuration	✗		
Suitable for workplace according to EN 12464-1	✗		
Lamp type	LED not exchangeable		
With light source	✓		
Lamp holder	Other		
Housing material	Aluminium		
Surface protection housing	Lacquered		
Housing colour	White		
Material cover	Plastic, opal		
Type of grid	None		
Voltage type	AC		
Type of control gear	LED operating device current-controlled		
With control gear	✓		
Dimming phase cut-on (leading edge)	✗		
Dimming programmable	✗		
Dimming RF	✗		
Dimming Touch and Dim	✗		
Dimming Sine Wave Reduction	✗		
Dimming Zigbee	✗		
Dimming with push-button	✗		
Light distributor	Diffuser lens/optic/panel		
Light distribution	Symmetric		
Beam angle	>80° - Extreme wide beam		

LED Pro-Ceiling

PAGE 2/2

LED Pro-Ceiling ø 240 mm (surface mount)

40001123

EAN: 8720615507450

PRODUCT FEATURES

(continuation)

Degree of protection (IP)	IP40
Impact strength	IK08
Emergency power supply integrated	✗
Suitable for emergency lighting	✗
With air slots	✗
Type of wiring	Ending
Connection type	Screwed terminal
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No
Operation by Bluetooth	✗
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Compatible with Amazon Alexa	✗
IFTTT support available	✗