

LED Pro-Space

PAGE 1/2


LED Pro-Space square 125 mm

40004280

EAN: 8720604743227

EXPERIENCE THE TIMELESS ELEGANCE OF MINIMALISM WITH PRO-SPACE FRAMELESS LUMINAIRES

The LED Pro-Space is a sleek and timeless recessed fixture, with a very low installation depth. Due to its trimless design it integrates flawlessly in any ceiling, while the IP66 classification enables use in humid places without difficulty.



PRODUCT FEATURES

Suitable for wall mounting	✓	Nominal voltage	220 240 Volt
Suitable for wall mounting	✓	Nominal current	500 500 Milliampere
Suitable for suspended mounting	✗	Rated lifetime L70/B50 at 25 °C	50000 Hour
Suitable for ceiling mounting	✓	Rated ambient temperature according to IEC 62722-2-1	-20 50 Degrees celsius
Suitable for built-in mounting	✓	Luminaire efficacy	75.5 Lumen/Watt
Suitable for surface mounting	✗	Rated luminous flux according to IEC 62722-2-1	830 Lumen
Suitable for light line configuration	✗	Max. system power	11 Watt
Suitable for workplace according to EN 12464-1	✗	Colour temperature	3000 3000 Kelvin
Lamp type	LED not exchangeable	Power factor	0.9
With light source	✓	Width	125 Millimetre
Lamp holder	Other	Height/depth	20 Millimetre
Housing material	Aluminium	Length	125 Millimetre
Surface protection housing	Other	Built-in length	105 Millimetre
Housing colour	White	Built-in width	105 Millimetre
Material cover	Plastic, opal	Built-in height/depth	20 Millimetre
Type of grid	None	Unified Glare Ratio (UGR)	24
Voltage type	AC		
Type of control gear	LED operating device current-controlled		
With control gear	✓		
Dimming 0-10 V	✗		
Dimming 1-10 V	✗		
Dimming DALI	✗		
Dimming DMX	✗		
Dimming DSI	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		
Dimming manufacturer's proprietary system	✗		
Dimming mains voltage modulation	✗		

LED Pro-Space

PAGE 2/2

LED Pro-Space square 125 mm

40004280

EAN: 8720604743227

PRODUCT FEATURES

(continuation)

Dimming phase cut-off (trailing edge)	✗
Dimming phase cut-on (leading edge)	✗
Dimming programmable	✗
Dimming potentiometer (integrated)	✗
Dimming RF	✗
Dimming Touch and Dim	✗
Dimming Sine Wave Reduction	✗
Dimming Zigbee	✗
Dimming with push-button	✗
Light distributor	Diffuser lens/optic/panel
No dim function	✓
Light distribution	Symmetric
Dimming depending on control gear	✓
Beam angle	>80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM4
Light outlet	Direct
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP66
Impact strength	IK08
Protection class according to IEC 61140	II
Emergency power supply integrated	✗
Suitable for emergency lighting	✗
With movement sensor	✗
With light sensor	✗
Covering of the luminaire with thermally insulating material possible	✗
With air slots	✗
Colour of light according to EN 12464-1	Warm white <3300 K
Colour of light	White
Colour rendering index CRI	80-89
Type of wiring	Ending
Connection type	Screwed terminal
Operation by Bluetooth	✗