

## LED Pro-Fit

PAGE 1/2


LED Pro-Fit white (semi shielded)

# 40010323

EAN: 8720604744316

### ROBUST AND STYLISHLY DESIGNED CEILING AND WALL FIXTURES WITH ENERGY SAVING OPTIONS

The Pro-Fit series includes two robust and sleekly designed ceiling and wall fixtures. The Pro-Fit is extremely suitable for housing construction, for use in portals, corridors, galleries and storerooms and on the outside of buildings to illuminate the front and back doors. It is also a perfect one-to-one replacement for the most commonly used conventional variants, where the dimensions make painting unnecessary in many cases.



## PRODUCT FEATURES

|                                           |                                         |                                 |                       |
|-------------------------------------------|-----------------------------------------|---------------------------------|-----------------------|
| Suitable for wall mounting                | ✓                                       | Nominal voltage                 | 240 240 Volt          |
| Suitable for wall mounting                | ✓                                       | Rated lifetime L70/B50 at 25 °C | 100000 Hour           |
| Suitable for suspended mounting           | ✗                                       | Luminaire efficacy              | 90 Lumen/Watt         |
| Suitable for ceiling mounting             | ✓                                       | Max. system power               | 8 Watt                |
| Suitable for built-in mounting            | ✗                                       | Colour temperature              | 3000 4000 Kelvin      |
| Suitable for surface mounting             | ✓                                       | Power factor                    | 0.8                   |
| Suitable for light line configuration     | ✗                                       | Width                           | 140 Millimetre        |
| Lamp type                                 | LED exchangeable                        | Height/depth                    | 110 Millimetre        |
| With light source                         | ✓                                       | Length                          | 280 Millimetre        |
| Lamp holder                               | Other                                   | Number of poles                 | 2                     |
| Housing material                          | Plastic                                 | Conductor cross section         | 1.5 Square millimetre |
| Surface protection housing                | Untreated                               |                                 |                       |
| Housing colour                            | White                                   |                                 |                       |
| Material cover                            | Plastic, transparent                    |                                 |                       |
| Type of grid                              | None                                    |                                 |                       |
| Voltage type                              | AC                                      |                                 |                       |
| Type of control gear                      | LED operating device current-controlled |                                 |                       |
| With control gear                         | ✓                                       |                                 |                       |
| Exchangeable control gear                 | ✗                                       |                                 |                       |
| Dimming 0-10 V                            | ✗                                       |                                 |                       |
| Dimming 1-10 V                            | ✗                                       |                                 |                       |
| Dimming DALI                              | ✗                                       |                                 |                       |
| Dimming DALI-2                            | ✗                                       |                                 |                       |
| Dimming DMX                               | ✗                                       |                                 |                       |
| Dimming GPRS                              | ✗                                       |                                 |                       |
| Dimming LineSwitch                        | ✗                                       |                                 |                       |
| Dimming DSI                               | ✗                                       |                                 |                       |
| Dimming manufacturer's proprietary system | ✗                                       |                                 |                       |
| Dimming mains voltage modulation          | ✗                                       |                                 |                       |
| Dimming phase cut-off (trailing edge)     | ✗                                       |                                 |                       |

## LED Pro-Fit

PAGE 2/2

LED Pro-Fit white (semi shielded)

# 40010323

EAN: 8720604744316

### PRODUCT FEATURES

(continuation)

|                                                                       |                           |
|-----------------------------------------------------------------------|---------------------------|
| Dimming phase cut-on (leading edge)                                   | ✗                         |
| Dimming programmable                                                  | ✗                         |
| Dimming potentiometer (integrated)                                    | ✗                         |
| Dimming RF                                                            | ✗                         |
| Dimming Sine Wave Reduction                                           | ✗                         |
| Dimming Touch and Dim                                                 | ✗                         |
| Dimming Zigbee                                                        | ✗                         |
| Dimming with push-button                                              | ✗                         |
| No dim function                                                       | ✓                         |
| Dimming depending on control gear                                     | ✗                         |
| Light distributor                                                     | Other                     |
| Light distribution                                                    | Symmetric                 |
| Beam angle                                                            | > 80° - Extreme wide beam |
| Colour consistency (McAdam ellipse)                                   | SDCM3                     |
| Light outlet                                                          | Direct                    |
| Containing product according to 2019/2020/EU                          | ✓                         |
| Energy efficiency class of the built-in lamp                          | A++, A+, A (LED)          |
| Degree of protection (IP)                                             | IP66                      |
| Impact strength                                                       | IK10                      |
| Protection class according to IEC 61140                               | II                        |
| Emergency power supply integrated                                     | ✓                         |
| Suitable for emergency lighting                                       | ✓                         |
| With movement sensor                                                  | ✓                         |
| With light sensor                                                     | ✗                         |
| Covering of the luminaire with thermally insulating material possible | ✓                         |
| With air slots                                                        | ✗                         |
| Filament test according to IEC 60695-2-11                             | 850 °C - 30 s             |
| Colour of light                                                       | White                     |
| Colour rendering index CRI                                            | 80-89                     |
| Type of wiring                                                        | Ending                    |
| Connection type                                                       | Push-in clamp             |
| Operation by Bluetooth                                                | ✗                         |
| Compatible with Apple HomeKit                                         | ✗                         |
| Compatible with Google Assistant                                      | ✗                         |
| Compatible with Amazon Alexa                                          | ✗                         |
| IFTTT support available                                               | ✗                         |