

LED Pro-Bay Multi

PAGE 1/2

Pro-Bay Multi Lighting Controls

40643516

EAN: 8721063007516

NEXT LEVEL Highbay Luminaire that excels in Price, Performance and Usability

The Pro-Bay Multi is an outlier in many respects. Its exceptionally high luminous efficacy of up to 195 lm/W results in significant energy savings. In addition, 3 adjustable levels of brightness and a color temperature that can be set to 3000, 4000 or 5000 K maximize its usability. Finally, Pro-Bay Multi accessories, such as PIR or radar-controlled motion detectors, a twilight switch or Casambi module offer the benefits and comfort of an intelligent lighting solution literally in an instant.



PRODUCT FEATURES

Model	Movement sensor	Scan angle	360 Degrees
Sensor type	Passive infrared	Optimum mounting height	12 Metre
Movement sensor/presence detector technology	Passive infrared	Max. reach sideways	4 Metre
With DALI interface	✗	Max. reach frontally	12 Metre
Constant light control	✓	Diameter reach on floor	8 Metre
HVAC-control	✗	RAL-number (similar)	9016
Forced switch on	✗	Nominal voltage	12 Volt
Forced switch off	✗	Nominal voltage	12 12 Volt
Animal zone	✗	Min. switch-on time	5 Second
Creep-under protection	✗	Max. duty cycle	90 Minute
Background monitoring	✗	Switch-off delay	0 Second
Networkable	✗	Switching-on delay	0 Second
Staircase light controller	✗	Detection angle horizontal	30 120 Degrees
Bridging switch	✗	Pivoting range sensor, horizontal	0 0 Degrees
Remote operation	✓	Pivoting range sensor, vertical	0 0 Degrees
With remote control	✓	Response value luminosity	2 400 Lux
Response value sensitivity adjustable	✓	Max. switching power	200 Watt
Response value luminosity adjustable	✓	Max. switching power LED	200 Watt
With signal unit	✗	Number of switching zones	1
Teach-function for response value luminosity	✗	Temperature	-20 60 Degrees celsius
Dim function with dimmer basic element	✗	Max. starting current	80 Ampere
Suitable for wall mounting	✗	Control current	30 Milliampere
Mounting method	Other	Ambient temperature	-20 60 Degrees celsius
Suitable for ceiling mounting	✗	Height	43.1 Millimetre
Ceiling built-in mounting without installation box	✗	Diameter	47.9 Millimetre
Suitable for wall mounting	✗		
Connection type	Other		
Material	Plastic		
Material quality	Other		

LED Pro-Bay Multi

PAGE 2/2

Pro-Bay Multi Lighting Controls

40643516

EAN: 8721063007516

PRODUCT FEATURES

(continuation)

Halogen free	✗
Surface protection	Other
Surface finishing	Matt
Anti-bacterial treatment	✗
Colour	White
Transparent	✗
Degree of protection (IP)	IP65
Impact strength	IK02
Voltage type	DC
Suitable for C-load	✗
Substation input	✓
With alarm function	✗
With acoustic sensor	✗
With connection cable	✗
Compatible with Apple HomeKit	✗
Compatible with Google Assistant	✗
Compatible with Amazon Alexa	✗
Compatible with Casambi	✗
IFTTT support available	✗