

## LED Pro-Flood

PAGE 1/1


LED Pro-Flood 150W

# 41060764

EAN: 8720604748581

### BIG PERFORMANCE IN A COMPACT DESIGN

The robust Prolumia Pro-Flood series consists of functional and compactly designed spotlights in five different dimensions for indoor and outdoor applications. Available with symmetrical and asymmetrical optics. Ideally suited to illuminate business areas, parking lots, sports fields and facades, amongst others.



### PRODUCT FEATURES

|                                         |                                         |                                                      |                        |
|-----------------------------------------|-----------------------------------------|------------------------------------------------------|------------------------|
| Suitable for surface mounting           | ✓                                       | Suitable for number of light sources                 | 1                      |
| Suitable for built-in mounting          | ✗                                       | Nominal voltage                                      | 220 240 Volt           |
| Suitable for wall mounting              | ✓                                       | Rated ambient temperature according to IEC 62722-2-1 | -30 50 Degrees celsius |
| Suitable for wall mounting              | ✓                                       | Max. system power                                    | 150 Watt               |
| Suitable for suspended mounting         | ✗                                       | Luminous flux                                        | 18750 18750 Lumen      |
| Suitable for ceiling mounting           | ✓                                       | Colour temperature                                   | 4000 4000 Kelvin       |
| Suitable for traverse mounting          | ✓                                       | Length                                               | 67 Millimetre          |
| Suitable for pedestal/floor mounting    | ✓                                       | Width                                                | 302 Millimetre         |
| Suitable for light-track mounting       | ✗                                       | Height/depth                                         | 360 Millimetre         |
| Suitable for clamp-mounting             | ✓                                       |                                                      |                        |
| Adjustability                           | Rotatable                               |                                                      |                        |
| With movement sensor                    | ✗                                       |                                                      |                        |
| With light sensor                       | ✗                                       |                                                      |                        |
| Lamp type                               | LED not exchangeable                    |                                                      |                        |
| With light source                       | ✓                                       |                                                      |                        |
| Lamp holder                             | Other                                   |                                                      |                        |
| Housing material                        | Aluminium                               |                                                      |                        |
| Surface protection                      | Powder coating                          |                                                      |                        |
| Housing colour                          | Black                                   |                                                      |                        |
| Material cover                          | Glass transparent                       |                                                      |                        |
| Surface brushed                         | ✗                                       |                                                      |                        |
| Voltage type                            | AC                                      |                                                      |                        |
| Type of control gear                    | LED operating device current-controlled |                                                      |                        |
| With control gear                       | ✓                                       |                                                      |                        |
| No dim function                         | ✓                                       |                                                      |                        |
| Reflector                               | None                                    |                                                      |                        |
| Light distribution                      | Symmetric                               |                                                      |                        |
| Light outlet                            | Direct                                  |                                                      |                        |
| Degree of protection (IP)               | IP66                                    |                                                      |                        |
| Protection class according to IEC 61140 | I                                       |                                                      |                        |
| Colour of light                         | White                                   |                                                      |                        |