


LED Pro-Rio Tracklight E

41106243

EAN: 8720615501786

VERSATILE AND FLEXIBLE LIGHTING SOLUTION

The LED Pro-Rio Tracklight series are incredibly beautiful spots that are very suitable for use in, for example, shops, museums and art galleries. Illuminate your products and objects with these spots perfectly for a superb presentation. Mount the fixtures to the wall, the ceiling or - even better - fit them on a rail, where you can create endless positioning possibilities.



PRODUCT FEATURES

| | | | |
|---------------------------------------|---|--|-----------------------|
| Suitable for surface mounting | ✓ | Nominal voltage | 220 240 Volt |
| Suitable for built-in mounting | ✗ | Rated lifetime L70/B50 at 25 °C | 50000 Hour |
| Suitable for wall mounting | ✓ | Rated ambient temperature according to IEC 62722-2-1 | -5 35 Degrees celsius |
| Suitable for wall mounting | ✓ | Max. system power | 45 Watt |
| Suitable for suspended mounting | ✗ | Luminous flux | 4350 4350 Lumen |
| Suitable for ceiling mounting | ✓ | Rated luminous flux according to IEC 62722-2-1 | 4350 Lumen |
| Suitable for traverse mounting | ✗ | Lamp efficacy | 96.67 Lumen/Watt |
| Suitable for pedestal/floor mounting | ✗ | Colour temperature | 2700 2700 Kelvin |
| Suitable for light-track mounting | ✓ | Power factor | 0.9 |
| Suitable for clamp-mounting | ✗ | Length | 201 Millimetre |
| Suitable for low voltage cable system | ✗ | Height/depth | 148 Millimetre |
| Adjustability | Rotatable | Outer diameter | 120 Millimetre |
| With movement sensor | ✗ | Number of poles | 3 |
| With light sensor | ✗ | Luminaire efficacy | 96.67 Lumen/Watt |
| Lamp type | LED not exchangeable | Unified Glare Ratio (UGR) | 14 |
| With light source | ✓ | | |
| Lamp holder | Other | | |
| Housing material | Aluminium | | |
| Housing colour | White | | |
| Material cover | Without cover | | |
| Voltage type | AC | | |
| Type of control gear | LED operating device current-controlled | | |
| With control gear | ✓ | | |
| Dimming depending on control gear | ✗ | | |
| Dimming 0-10 V | ✗ | | |
| Dimming 1-10 V | ✗ | | |
| Dimming DALI-2 | ✗ | | |
| Dimming DALI | ✗ | | |
| Dimming DMX | ✗ | | |
| Dimming DSI | ✗ | | |

LED Pro-Rio Tracklight

LED Pro-Rio Tracklight E

41106243

EAN: 8720615501786

PRODUCT FEATURES

(continuation)

| | |
|---|----------------------|
| Dimming GPRS | ✘ |
| Dimming potentiometer (integrated) | ✘ |
| Dimming LineSwitch | ✘ |
| Dimming manufacturer's proprietary system | ✘ |
| Dimming mains voltage modulation | ✘ |
| Dimming phase cut-off (trailing edge) | ✘ |
| Dimming phase cut-on (leading edge) | ✘ |
| Dimming programmable | ✘ |
| Dimming RF | ✘ |
| Dimming Sine Wave Reduction | ✘ |
| Dimming Touch and Dim | ✘ |
| Dimming Zigbee | ✘ |
| No dim function | ✓ |
| Dimming with push-button | ✘ |
| Light distributor | Reflector |
| Light distribution | Symmetric |
| Beam angle | 21-40° - Medium beam |
| Light outlet | Direct |
| Energy efficiency class of the built-in lamp | A++, A+, A (LED) |
| Degree of protection (IP) | IP20 |
| Protection class according to IEC 61140 | I |
| Colour of light | White |
| Colour of light adjustable | No |
| Colour rendering index CRI | 90-100 |
| Luminous flux adjustable | No |
| Beam angle adjustable | No |
| Type of wiring | Ending |
| Emergency power supply integrated | ✘ |
| Connection type | Other |
| Suitable for workplace according to EN 12464-1 | ✘ |
| Covering of the luminaire with thermally insulating material possible | ✘ |
| Compatible with Apple HomeKit | ✘ |
| Compatible with Google Assistant | ✘ |
| Compatible with Amazon Alexa | ✘ |