


LED Pro-Rio Tracklight E

41106551

EAN: 8720615501892

VERSATILE AND FLEXIBLE LIGHTING SOLUTION

The LED Pro-Rio Tracklight series are incredibly beautiful spots that are very suitable for use in, for example, shops, museums and art galleries. Illuminate your products and objects with these spots perfectly for a superb presentation. Mount the fixtures to the wall, the ceiling or - even better - fit them on a rail, where you can create endless positioning possibilities.



PRODUCT FEATURES

Suitable for surface mounting	✓	Nominal voltage	220 240 Volt
Suitable for built-in mounting	✗	Rated lifetime L70/B50 at 25 °C	50000 Hour
Suitable for wall mounting	✓	Rated ambient temperature according to IEC 62722-2-1	-5 35 Degrees celsius
Suitable for wall mounting	✓	Max. system power	45 Watt
Suitable for suspended mounting	✗	Luminous flux	5050 5050 Lumen
Suitable for ceiling mounting	✓	Rated luminous flux according to IEC 62722-2-1	5050 Lumen
Suitable for traverse mounting	✗	Lamp efficacy	112.22 Lumen/Watt
Suitable for pedestal/floor mounting	✗	Colour temperature	4000 4000 Kelvin
Suitable for light-track mounting	✓	Power factor	0.9
Suitable for clamp-mounting	✗	Length	201 Millimetre
Suitable for low voltage cable system	✗	Height/depth	148 Millimetre
Adjustability	Rotatable	Outer diameter	120 Millimetre
With movement sensor	✗	Number of poles	3
With light sensor	✗	Luminaire efficacy	112.22 Lumen/Watt
Lamp type	LED not exchangeable	Unified Glare Ratio (UGR)	14
With light source	✓		
Lamp holder	Other		
Housing material	Aluminium		
Housing colour	Black		
Material cover	Without cover		
Voltage type	AC		
Type of control gear	LED operating device current-controlled		
With control gear	✓		
Dimming depending on control gear	✗		
Dimming 0-10 V	✗		
Dimming 1-10 V	✗		
Dimming DALI-2	✗		
Dimming DALI	✗		
Dimming DMX	✗		
Dimming DSI	✗		

LED Pro-Rio Tracklight

LED Pro-Rio Tracklight E

41106551

EAN: 8720615501892

PRODUCT FEATURES

(continuation)

Dimming GPRS	✘
Dimming potentiometer (integrated)	✘
Dimming LineSwitch	✘
Dimming manufacturer's proprietary system	✘
Dimming mains voltage modulation	✘
Dimming phase cut-off (trailing edge)	✘
Dimming phase cut-on (leading edge)	✘
Dimming programmable	✘
Dimming RF	✘
Dimming Sine Wave Reduction	✘
Dimming Touch and Dim	✘
Dimming Zigbee	✘
No dim function	✓
Dimming with push-button	✘
Light distributor	Reflector
Light distribution	Symmetric
Beam angle	41-80° - Wide beam
Light outlet	Direct
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP20
Protection class according to IEC 61140	I
Colour of light	White
Colour of light adjustable	No
Colour rendering index CRI	90-100
Luminous flux adjustable	No
Beam angle adjustable	No
Type of wiring	Ending
Emergency power supply integrated	✘
Connection type	Other
Suitable for workplace according to EN 12464-1	✘
Covering of the luminaire with thermally insulating material possible	✘
Compatible with Apple HomeKit	✘
Compatible with Google Assistant	✘
Compatible with Amazon Alexa	✘