## **PROLUMIA**®

LED Strip Bronze PAGE 1/1


LED Strip Bronze Color

# 46180110 EAN: 8720615504268

## FOR INDOOR USE

The new LED strips Bronze are practical and can be used endlessly. Due to the white 2835 LEDs with better cooling, the light depreciation over time is reduced to a minimum, resulting in a longer lifetime. Thanks to the different versions it is possible to create different effects by illuminating coves, niches or other places where indirect lighting perfectly fits. Also, due to the higher efficiency these LED strips lend themselves perfectly for general lighting.





## PRODUCT FEATURES

IFTTT support available

Voltage type     DC     Lamp voltage     22 26 W       Type of control gear     LED operating device voltage-controlled     Beam angle     120 E       Suitable for dimmer     ✓     Rated lifetime L70/B50 at 25 °C     50000 F       Exchangeable control gear     X     Max. system power     72 W       Degree of protection (IP)     IP20     Colour temperature     2700 2700 K       Degree of protection (NEMA)     1     Width     12 M	Lumen Volt Degrees Hour Watt
Lamp typeLED not exchangeableLuminous flux per meter555 LVoltage typeDCLamp voltage22 26 VType of control gearLED operating device voltage-controlledBeam angle120 CSuitable for dimmer✓Rated lifetime L70/B50 at 25 °C50000 FExchangeable control gearXMax. system power72 VDegree of protection (IP)IP20Colour temperature2700 2700 KDegree of protection (NEMA)1Width12 K	Lumen Volt Degrees Hour Watt Kelvin
Voltage typeDCLamp voltage22 26 MType of control gearLED operating device voltage-controlledBeam angle120 DSuitable for dimmer✓Rated lifetime L70/B50 at 25 °C50000 FExchangeable control gearXMax. system power72 MDegree of protection (IP)IP20Colour temperature2700 2700 KDegree of protection (NEMA)1Width12 M	Volt Degrees Hour Watt Kelvin
Type of control gear  LED operating device voltage-controlled  Beam angle  Rated lifetime L70/B50 at 25 °C  50000 F  Exchangeable control gear  ★  Max. system power  Degree of protection (IP)  Degree of protection (NEMA)  LED operating device voltage-controlled  Beam angle  Rated lifetime L70/B50 at 25 °C  50000 F  Max. system power  Colour temperature  2700 2700 K  Width	Degrees Hour Watt Kelvin
Suitable for dimmer✓Rated lifetime L70/B50 at 25 °C50000 FExchangeable control gear★Max. system power72 VDegree of protection (IP)IP20Colour temperature2700 2700 KDegree of protection (NEMA)1Width12 N	Hour Watt Kelvin
Exchangeable control gear	Watt Kelvin
Degree of protection (IP) IP20 Colour temperature 2700 2700 K Degree of protection (NEMA) 1 Width 12 K	Kelvin
Degree of protection (NEMA) 1 Width 12 M	
	Aillimetre
Colour of light RGBW Height/depth 3 N	viiiiiiietie
Togritadopar	Millimetre
Colour rendering index CRI 80-89 Length 5000 N	Millimetre
With end piece   ✓ Length of particular segments 200 N	Millimetre
With connection set	Millimetre
With protective cover X Number of poles 5	
Self-adhesive Sconductor cross section 0.75 S	Square millimetre
Type of wiring Ending	
Connection type Other	
Compatible with Apple HomeKit	
Compatible with Google Assistant	
Compatible with Amazon Alexa 💥	