


LED Lumiaflex II

46000221

EAN: 8720615503988

FLEXIBILNÍ INOVACE OSVTLENÍ, KTERÁ VYNIKÁ FORMOU A FUNKCÍ

Nová sada produkt LED Lumiaflex II značky Prolumia je ideální náhradou za tradiční skleněná neonová svítla. Toto nerozbitné a vodotěsné lineární osvětlení je k dispozici v mnoha barevných variantách a má jednoduchý světelný výkon. LED Lumiaflex II lze snadno ohnout, a proto je vhodné pro tvorbu písmen a obrázků.



VLASTNOSTI PRODUKTU

Model	Hose	Number of nodes per meter	60
Mounting method	Surface mounting/recessed mounting	Lamp power per meter	7,2 Watt
Lamp type	LED not exchangeable	Luminous flux per meter	120 Lumen
Voltage type	DC	Lamp voltage	22 26 Volt
Type of control gear	LED operating device voltage-controlled	Beam angle	160 Degrees
Suitable for dimmer	✓	Rated life time L70/B50 at 25 °C	50000 Hour
Exchangeable control gear	✗	Rated life time L80/B10 at 25 °C	10 Hour
Degree of protection (IP)	IP68	Max. system power	120 Watt
Degree of protection (NEMA)	3	Width	11,5 Millimetre
Colour of light	Yellow	Height/depth	29 Millimetre
Colour rendering index CRI	20-39	Length	10000 Millimetre
With end piece	✗	Diameter	11,5 Millimetre
With connection set	✗	Lowest bending radius	120 Millimetre
With protective cover	✓	Length of particular segments	125 Millimetre
Self-adhesive	✗	Number of poles	2
Type of wiring	Ending	Conductor cross section	0,75 Square millimetre
Connection type	Other		
Compatible with Apple HomeKit	✗		
Compatible with Google Assistant	✗		
Compatible with Amazon Alexa	✗		
IFTTT support available	✗		