

LED I-Panel drivers

40000522

EAN: 8720604740219

ALTERNATIVE FOR TRADITIONAL RECESSED FLUORESCENCE LUMINAIRES

The different kind of LED power supplies are available for both indoor and outdoor applications (waterproof). Thanks to the relatively thin size of the power supplies, it can easily be concealed under a shelf, in a cabinet or behind a wall.



PRODUCT FEATURES

Model	Dynamic	Output voltage	2 44 Volt
Suitable for outdoor use	✗	Output current	1250 1250 Milliampere
Dimming 0-10 V	✗	Output power	55 55 Watt
Dimming 1-10 V	✓	Length	127 Millimetre
Dimming DALI	✓	Width	75 Millimetre
Dimming DSI	✗	Height	30 Millimetre
Dimming DMX	✗		
Dimming potentiometer (integrated)	✗		
Dimming GPRS	✗		
Dimming LineSwitch	✗		
Dimming manufacturer's proprietary system	✗		
Dimming mains voltage modulation	✗		
Dimming phase cut-off	✗		
Dimming phase cut-on	✗		
Dimming programmable	✗		
Dimming RF	✗		
Dimming Sine Wave Reduction	✗		
Dimming Touch and Dim	✗		
Dimming Zigbee	✗		
Dimming with push-button	✓		
Constant light output (CLO)	✗		
No dim function	✗		
Housing	Plastic housing		
Suitable for constant current	✓		
Suitable for constant voltage	✗		
Suitable for DC-voltage (primary side)	✗		
Degree of protection (IP)	IP20		
Protection class	II		
Operation by Bluetooth	✗		
Compatible with Apple HomeKit	✗		

LED drivers

LED I-Panel drivers

40000522

EAN: 8720604740219

PRODUCT FEATURES

(continuation)

Compatible with Google Assistant	✘
Compatible with Amazon Alexa	✘
Compatible with Casambi	✘
IFTTT support available	✘