

LED I-Panel

LED I-Panel drivers

40000526

EAN: 8720604740240

ALTERNATIVE FOR TRADITIONAL RECESSED FLUORESCENCE LUMINAIRES

The LED I-Panel series are a good alternative for traditional recessed fluorescence luminaires. The neat lines and the limited height give these series a modern and timeless character. Through the various installation options; surface mounted, recessed and suspended, the LED I-panel has a very wide field of application.



PRODUCT FEATURES

| | | | |
|---|-----------------|----------------|----------------------|
| Model | Dynamic | Output voltage | 2 74 Volt |
| Suitable for outdoor use | ✗ | Output current | 350 1050 Milliampere |
| Dimming 0-10 V | ✓ | Output power | 25 60 Watt |
| Dimming 1-10 V | ✓ | Length | 125 Millimetre |
| Dimming DALI | ✓ | Width | 78 Millimetre |
| Dimming DSI | ✗ | Height | 22 Millimetre |
| Dimming DMX | ✗ | | |
| Dimming potentiometer (integrated) | ✗ | | |
| Dimming GPRS | ✗ | | |
| Dimming LineSwitch | ✗ | | |
| Dimming manufacturer's proprietary system | ✗ | | |
| Dimming mains voltage modulation | ✗ | | |
| Dimming phase cut-off | ✗ | | |
| Dimming phase cut-on | ✗ | | |
| Dimming programmable | ✗ | | |
| Dimming RF | ✗ | | |
| Dimming Sine Wave Reduction | ✗ | | |
| Dimming Touch and Dim | ✗ | | |
| Dimming Zigbee | ✗ | | |
| Dimming with push-button | ✓ | | |
| Constant light output (CLO) | ✗ | | |
| No dim function | ✗ | | |
| Housing | Plastic housing | | |
| Suitable for constant current | ✓ | | |
| Suitable for constant voltage | ✗ | | |
| Suitable for DC-voltage (primary side) | ✗ | | |
| Degree of protection (IP) | IP20 | | |
| Protection class | II | | |
| Operation by Bluetooth | ✗ | | |
| Compatible with Apple HomeKit | ✗ | | |

LED I-Panel

LED I-Panel drivers

40000526

EAN: 8720604740240

PRODUCT FEATURES

(continuation)

| | |
|----------------------------------|---|
| Compatible with Google Assistant | ✘ |
| Compatible with Amazon Alexa | ✘ |
| Compatible with Casambi | ✘ |
| IFTTT support available | ✘ |