

LED I-Panel PAGE 1/2

Output voltage

Output current

Output power

Length

Width Height

LED I-Panel drivers

40000534

EAN: 8720604740264

ALTERNATIVE FOR TRADITIONAL RECESSED FLUORESCENCE LUMINAIRES

The LED I-Panel series are a good alternative for traditional recessed fluorescence luminaires. The neat lines and the limited height give these series a modern and timeless character. Through the various installation options; surface mounted, recessed and suspended, the LED I-panel has a very wide field of application.



PRODUCT FEATURES

| Model | Dynamic |
|---|------------------|
| Suitable for outdoor use | × |
| Dimming 0-10 V | × |
| Dimming 1-10 V | × |
| Dimming DALI | ✓ |
| Dimming DSI | × |
| Dimming DMX | × |
| Dimming potentiometer (integrated) | × |
| Dimming GPRS | × |
| Dimming LineSwitch | × |
| Dimming manufacturer's proprietary system | × |
| Dimming mains voltage modulation | * |
| Dimming phase cut-off | × |
| Dimming phase cut-on | × |
| Dimming programmable | * |
| Dimming RF | * |
| Dimming Sine Wave Reduction | * |
| Dimming Touch and Dim | * |
| Dimming Zigbee | * |
| Dimming Ligbee Dimming with push-button | * |
| Constant light output (CLO) | * |
| No dim function | * |
| Housing | Plastic housing |
| Suitable for constant current | riastic flousing |
| Suitable for constant current | * |
| | * |
| Suitable for DC-voltage (primary side) | ** |
| Degree of protection (IP) | IP20 |
| Protection class | II . |
| Operation by Bluetooth | × |
| Compatible with Apple HomeKit | × |

3|49 Volt

12|20 Watt

250|700 Milliampere

111 Millimetre 52 Millimetre

22 Millimetre



LED I-Panel PAGE 2/2

LED I-Panel drivers

40000534 EAN: 8720604740264

PRODUCT FEATURES

(continuation)

| Compatible with Google Assistant | × |
|----------------------------------|---|
| Compatible with Amazon Alexa | × |
| Compatible with Casambi | × |
| IFTTT support available | × |