PROLUMIA[®]

LED Pro-Cone


Pro-Cone Lens type 3

41380123 EAN: 8720874790334

VANDAL RESISTANT AND CIRCULAIR LED CONE FIXTURE FOR OPTIMAL PUBLIC LIGHTING

The Pro-Cone is a vandal resistand and circular LED cone fixture that guarantees maximum and optimal illumination of the public space. This without unnecessary light hindrance and light pollution, because it's possible to choose of 5 different lens types. Because of this, it is possible to create light as desired. Due to the many options, the long life span, the high efficiency and the choice of the different lenses, the Pro-Cone is very widely applicable. Ideal for use in residential areas, parking lots, cycle paths, squares and downtown areas.





PRODUCT FEATURES

		Nominal voltage	220 240 Volt
Lamp type LED exchangea	ble	LED nominal current at constant current	228 228 Milliampere
With light source		Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	90 Percentage
Lamp holder None		Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq)	80 Percentage
Housing material Aluminium		Rated life time L70/B50 at 25 °C	150000 Hour
Surface protection Other		Rated life time L80/B10 at 25 °C	110000 Hour
Housing colour Black		Suitable for spigot size	60 60 Millimetre
Material cover Plastic matt/sati	nized	Rated life time L90/B10 at 25 °C	55000 Hour
Voltage type AC		Rated ambient temperature according to IEC 62722-2-1	-25 50 Degrees celsius
Type of control gear LED operating of	device current-controlled	Cable length	5 Metre
With control gear 🗸		Max. system power	13 Watt
Exchangeable control gear		Rated luminous flux according to IEC 62722-2-1	1600 Lumen
Dimming 0-10 V 🗱		Luminaire efficacy	121 Lumen/Watt
Dimming 1-10 V 🖌		Colour temperature	3000 3000 Kelvin
Dimming DALI X		Power factor	0.83
Dimming DMX X		Height/depth	415 Millimetre
Dimming DSI 🗱		Diameter	540 Millimetre
Dimming potentiometer (integrated)		Number of poles	3
Dimming LineSwitch		Conductor cross section	1 Square millimetre
Dimming GPRS X			
Dimming manufacturer's proprietary system X			
Dimming mains voltage modulation			
Dimming phase cut-off 🛛 🗶			
Dimming phase cut-on			
Dimming programmable			
Dimming RF 🗶			
Dimming Sine Wave Reduction			

PAGE 1/2

PROLUMIA[®]

LED Pro-Cone

Pro-Cone Lens type 3

41380123 EAN: 8720874790334

PRODUCT FEATURES (continuation)

×
x
x
x
Focal lens
SDCM3
A++, A+, A (LED)
IP66
3
IK10
1
None
×
×
×
✓
White
70-79
Ending
×
×
Screwed terminal
×
×
**

PAGE 2/2