# **PROLUMIA**<sup>®</sup>

#### **LED Pro-Cone**


Pro-Cone Lens type 1

# 41380205 EAN: 8720874790501

### VANDAL RESISTANT AND CIRCULAIR LED CONE FIXTURE FOR OPTIMAL PUBLIC LIGHTING

The Pro-Cone is a vandal resistand and circular LED cone fixture that guarantees maximum and optimal illumination of the public space. This without unnecessary light hindrance and light pollution, because it's possible to choose of 5 different lens types. Because of this, it is possible to create light as desired. Due to the many options, the long life span, the high efficiency and the choice of the different lenses, the Pro-Cone is very widely applicable. Ideal for use in residential areas, parking lots, cycle paths, squares and downtown areas.





#### PRODUCT FEATURES

Lamp type LED exchangeable	LED nominal current at constant current	
		278 278 Milliampere
Nith light source	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	90 Percentage
amp holder None	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq)	80 Percentage
Housing material Aluminium	Rated life time L70/B50 at 25 °C	150000 Hour
Surface protection Other	Rated life time L80/B10 at 25 °C	110000 Hour
Housing colour Black	Suitable for spigot size	60 60 Millimetre
Material cover Plastic matt/satinized	Rated life time L90/B10 at 25 °C	55000 Hour
Voltage type AC	Rated ambient temperature according to IEC 62722-2-1	-25 50 Degrees celsius
Type of control gear LED operating device current-control	olled Cable length	5 Metre
With control gear 🗸	Max. system power	14.5 Watt
Exchangeable control gear	Rated luminous flux according to IEC 62722-2-1	2000 Lumen
Dimming 0-10 V 🗶	Luminaire efficacy	137 Lumen/Watt
Dimming 1-10 V 🛛 🗸	Colour temperature	4000 4000 Kelvin
Dimming DALI 🗶	Power factor	0.9
Dimming DMX X	Height/depth	415 Millimetre
Dimming DSI 🛛 🗶	Diameter	540 Millimetre
Dimming potentiometer (integrated)	Number of poles	3
Dimming LineSwitch	Conductor cross section	1 Square millimetre
Dimming GPRS X		
Dimming manufacturer's proprietary		
Dimming mains voltage modulation		
Dimming phase cut-off 🛛 🗶		
Dimming phase cut-on 🗱		
Dimming programmable		
Dimming RF 🗶		
Dimming Sine Wave Reduction		

PAGE 1/2

# **PROLUMIA**<sup>®</sup>

### **LED Pro-Cone**

Pro-Cone Lens type 1

# 41380205 EAN: 8720874790501

#### **PRODUCT FEATURES** (continuation)

Dimming Touch and Dim	×
Dimming Zigbee	×
Dimming with push-button	×
No dim function	×
Light distributor	Focal lens
Colour consistency (McAdam ellipse)	SDCM3
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Degree of protection (IP)	IP66
Degree of protection (NEMA)	3
Impact strength	IK10
Protection class	I
Remote control	None
With radio control	×
Constant light output (CLO)	*
Constant light output (CLO) With light regulation program control	×
With light regulation program control	×
With light regulation program control With connection cable	× ×
With light regulation program control With connection cable Colour of light	× Vhite
With light regulation program control With connection cable Colour of light Colour rendering index CRI	<ul> <li>✗</li> <li>✓</li> <li>White</li> <li>70-79</li> </ul>
With light regulation program control With connection cable Colour of light Colour rendering index CRI Type of wiring	× White 70-79 Ending
With light regulation program control         With connection cable         Colour of light         Colour rendering index CRI         Type of wiring         Compatible with Apple HomeKit	X White 70-79 Ending X
With light regulation program control         With connection cable         Colour of light         Colour rendering index CRI         Type of wiring         Compatible with Apple HomeKit         Compatible with Google Assistant	X White 70-79 Ending X X
With light regulation program control         With connection cable         Colour of light         Colour rendering index CRI         Type of wiring         Compatible with Apple HomeKit         Compatible with Google Assistant         Connection type	<ul> <li>White</li> <li>70-79</li> <li>Ending</li> <li>X</li> <li>Screwed terminal</li> </ul>
With light regulation program control         With connection cable         Colour of light         Colour rendering index CRI         Type of wiring         Compatible with Apple HomeKit         Connection type         Compatible with Amazon Alexa	<ul> <li>White</li> <li>70-79</li> <li>Ending</li> <li>Screwed terminal</li> <li>X</li> </ul>

PAGE 2/2